

The `ltshipout` package*

Frank Mittelbach, L^AT_EX Project Team

December 6, 2021

Contents

1	Introduction	2
1.1	Overloading the <code>\shipout</code> primitive	2
1.2	Provided hooks	3
1.3	Legacy L ^A T _E X commands	4
1.4	Special commands for use inside the hooks	5
1.5	Provided LuaT _E X callbacks	5
1.6	Information counters	6
1.7	Debugging shipout code	6
2	Emulating commands from other packages	7
2.1	Emulating <code>atbegshi</code>	7
2.2	Emulating <code>everyshi</code>	8
2.3	Emulating <code>atenddvi</code>	8
2.4	Emulating <code>everypage</code>	8
3	The Implementation	9
3.1	Debugging	9
3.2	Handling the end of job hook	21
4	Legacy L^AT_EX 2_c interfaces	24
5	Internal commands needed elsewhere	24
6	Package emulation for compatibility	26
6.1	Package <code>atenddvi</code> emulation	26
6.2	Package <code>atbegshi</code> emulation	26
6.3	Package <code>everyshi</code> emulation	28
Index		28

*This package has version v1.0j dated 2021/06/09, © L^AT_EX Project.

1 Introduction

The code provides an interface to the `\shipout` primitive of T_EX which is called when a finished pages is finally “shipped out” to the target output file, e.g., the `.dvi` or `.pdf` file. A good portion of the code is based on ideas by Heiko Oberdiek implemented in his packages `atbegshi` and `atenddvi` even though the interfaces are somewhat different.¹

1.1 Overloading the `\shipout` primitive

`\shipout`

With this implementation T_EX’s `shipout` primitive is no longer available for direct use. Instead `\shipout` is running some (complicated) code that picks up the box to be shipped out regardless of how that is done, i.e., as a constructed `\vbox` or `\hbox` or as a box register.

It then stores it in a named box register. This box can then be manipulated through a set of hooks after which it is shipped out for real.

Each `shipout` that actually happens (i.e., where the material is not discarded for one or the other reason) is recorded and the total number is available in a readonly variable and in a L^AT_EX counter.

`\RawShipout`

This command implements a simplified `shipout` that bypasses the foreground and background hooks, e.g., only `shipout/firstpage` and `shipout/lastpage` are executed and the total `shipout` counters are incremented.

The command doesn’t use `\ShipoutBox` but its own private box register so that it can be used inside of `shipout` hooks to do some additional `shipout`s while already in the output routine with the current page being stored in `\ShipoutBox`. It does have access to `\ShipoutBox` if it is used in `shipout/before` (or `shipout/after`) and can use its content.

It is safe to use it in `shipout/before` or `shipout/after` but not necessarily in the other `shipout/...` hooks as they are intended for special processing.

`\ShipoutBox` `\l_shipout_box`

This box register is called `\ShipoutBox` (alternatively available via the L3 name `\l_-\shipout_box`).

This box is a “local” box and assignments to it should be done only locally. Global assignments (as done by some packages with older code where this is box is known as 255) may work but they are conceptually wrong and may result in errors under certain circumstances.

During the execution of `shipout/before` this box contains the accumulated material for the page, but not yet any material added by other `shipout` hooks. During execution of `shipout/after`, i.e., after the `shipout` has happened, the box also contains any background or foreground material.

Material from the hooks `shipout/firstpage` or `shipout/lastpage` is not included (but only used during the actual `shipout`) to facilitate reuse of the box data (e.g., `shipout/firstpage` material should never be added to a later page of the output).

¹Heiko’s interfaces are emulated by the kernel code, if a document requests his packages, so older documents will continue to work.

```
\l_shipout_box_ht_dim
\l_shipout_box_dp_dim
\l_shipout_box_wd_dim
\l_shipout_box_ht_plus_dp_dim
```

The shipout box dimensions are available in the L3 registers `\l_shipout_box_ht_dim`, etc. (there are no $\text{\LaTeX} 2\epsilon$ names).² These variables can be used inside the hook code for `shipout/before`, `shipout/foreground` and `shipout/background` if needed.

1.2 Provided hooks

```
shipout/before
shipout/after
shipout/foreground
shipout/background
shipout/firstpage
shipout/lastpage
```

The code for `\shipout` offers a number of hooks into which packages (or the user) can add code to support different use cases. These are:

shipout/before This hook is executed after the finished page has been stored in `\ShipoutBox` / `\l_shipout_box`). It can be used to alter that box content or to discard it completely (see `\DiscardShipoutBox` below).

You can use `\RawShipout` inside this hook for special use cases. It can make use of `\ShipoutBox` (which doesn't yet include the background and foreground material).

Note: It is not possible (or say advisable) to try and use this hook to typeset material with the intention to return it to main vertical list, it will go wrong and give unexpected results in many cases—for starters it will appear after the current page not before or it will vanish or the vertical spacing will be wrong!

shipout/background This hook adds a picture environment into the background of the page with the $(0,0)$ coordinate in the top-left corner using a `\unitlength` of `1pt`.

It should therefore only receive `\put` commands or other commands suitable in a `picture` environment and the vertical coordinate values would normally be negative.

Technically this is implemented by adding a zero-sized `\hbox` as the very first item into the `\ShipoutBox` containing that `picture` environment. Thus the rest of the box content will overprint what ever is typeset by that hook.

shipout/foreground This hook adds a picture environment into the foreground of the page with the $(0,0)$ coordinate in the top-left corner using a `\unitlength` of `1pt`.

Technically this is implemented by adding a zero-sized `\hbox` as the very last item into the `\ShipoutBox` and raising it up so that it still has its $(0,0)$ point in the top-left corner. But being placed after the main box content it will be typeset later and thus overprints it (i.e., is in the foreground).

shipout/firstpage The material from this hook is executed only once at the very beginning of the first output page that is shipped out (i.e., not discarded at the last minute). It should only contain `\special` or similar commands needed to direct post processors handling the `.dvi` or `.pdf` output.³

²Might need changing, but HO's version as strings is not really helpful I think).

³In $\text{\LaTeX} 2\epsilon$ that was already existing, but implemented using a box register with the name `\@begindvibox`.

This hook is added to the very first page regardless of how it is shipped out (i.e., with `\shipout` or `\RawShipout`).

shipout/lastpage The corresponding hook to add `\specials` at the very end of the output file. It is only executed on the very last page of the output file — or rather on the page that L^AT_EX believes is the last one. Again it is executed regardless of the `shipout` method.

It may not be possible for L^AT_EX to correctly determine which page is the last one without several reruns. If this happens and the hook is non-empty then L^AT_EX will add an extra page to place the material and also request a rerun to get the correct placement sorted out.

shipout/after This hook is executed after a `shipout` has happened. If the `shipout` box is discarded this hook is not looked at.

You can use `\RawShipout` inside this hook for special use cases and the main `\ShipoutBox` is still available at this point (but in contrast to `shipout/before` it now includes the background and foreground material).

Note: Just like `shipout/before` this hook is not meant to be used for adding typeset material back to the main vertical list—it might vanish or the vertical spacing will be wrong!

As mentioned above the hook `shipout/before` is executed first and can manipulate the prepared `shipout` box stored in `\ShipoutBox` or set things up for use in `\write` during the actual `shipout`. It is even run if there was a `\DiscardShipoutBox` request in the document.

The other hooks (except `shipout/after`) are added inside hboxes to the box being shipped out in the following order:

<code>shipout/firstpage</code>	only on the first page
<code>shipout/background</code>	
<code><boxed content of \ShipoutBox></code>	
<code>shipout/foreground</code>	
<code>shipout/lastpage</code>	only on the last page

If any of the hooks has no code then that particular no box is added at that point.

Once the (page) box has been shipped out the `shipout/after` hook is called (while you are still inside the output routine). It is not called if the `shipout` box was discarded.

In a document that doesn't produce pages, e.g., only makes `\typeouts`, none of the hooks are ever executed (as there is no `\shipout`) not even the `shipout/lastpage` hook.

If `\RawShipout` is used instead of `\shipout` then only the hooks `shipout/firstpage` and `shipout/lastpage` are executed (on the first or last page), all others are bypassed.

1.3 Legacy L^AT_EX commands

`\AtBeginDvi`
`\AtEndDvi`

`\AtBeginDvi` is the existing L^AT_EX 2_E interface to fill the `shipout/firstpage` hook. This is not really a good name as it is not just supporting `.dvi` but also `.pdf` output or `.xdv`.

`\AtEndDvi` is the counterpart that was not available in the kernel but only through the package `atenddvi`. It fills the `shipout/lastpage` hook.

As these two wrappers have been available for a long time we continue offering them. However, for new code we suggest using the high-level hook management commands directly instead of “randomly-named” wrappers. This will lead to code that is easier to understand and to maintain. For this reason we do not provide any other wrapper commands for the above hooks in the kernel.

1.4 Special commands for use inside the hooks

`\DiscardShipoutBox
\shipout_discard:`

`\AddToHookNext {shipout/before} {...\DiscardShipoutBox...}`

The `\DiscardShipoutBox` declaration (L3 name `\shipout_discard:`) requests that on the next shipout the page box is thrown away instead of being shipped to the `.dvi` or `.pdf` file.

Typical applications wouldn’t do this unconditionally, but have some processing logic that decides to use or not to use the page.

Note that if this declaration is used directly in the document it may depend on the placement to which page it applies, given that L^AT_EX output routine is called in an asynchronous manner! Thus normally one would use this only as part of the `shipout/before` code.

Todo: Once we have a new mark mechanism available we can improve on that and make sure that the declaration applies to the page that contains it.

In the `atbegshi` package there are a number of additional commands for use inside the `shipout/before` hook. They should normally not be needed any more as one can instead simply add code to the hooks `shipout/before`, `shipout/background` or `shipout/foreground`.⁴ If `atbegshi` gets loaded then those commands become available as public functions with their original names as given below.

1.5 Provided LuaT_EX callbacks

`pre_shipout_filter`

Under LuaT_EX the `pre_shipout_filter` Lua callback is provided which gets called immediately before the shipout primitive gets invoked. The signature is

```
function(<node> head)
    return true
end
```

The `head` is the list node corresponding to the box to be shipped out. The return value should always be `true`.

⁴If that assumption turns out to be wrong it would be trivial to change them to public functions (right now they are private).

1.6 Information counters

```
\ ReadonlyShipoutCounter  
\g_shipout_READONLY_int
```

```
\ifnum\ReadonlyShipoutCounter=...  
\int_use:N \g_shipout_READONLY_int % expl3 usage
```

This integer holds the number of pages shipped out up to now (including the one to be shipped out when inside the output routine). More precisely, it is incremented only after it is clear that a page will be shipped out, i.e., after the `shipout/before` hook (because that might discard the page)! In contrast `shipout/after` sees the incremented value.

Just like with the page counter its value is only accurate within the output routine. In the body of the document it may be off by one as the output routine is called asynchronously!

Also important: it *must not* be set, only read. There are no provisions to prevent that restriction, but if you manipulate it, chaos will be the result. To emphasize this fact it is not provided as a L^AT_EX counter but as a T_EX counter (i.e., a command), so `\Alph{\ReadonlyShipoutCounter}` etc, would not work.

```
totalpages  
\g_shipout_TOTALPAGES_int
```

```
\arabic{totalpages}  
\int_use:N \g_shipout_TOTALPAGES_int % expl3 usage
```

In contrast to `\ReadonlyShipoutCounter`, the `totalpages` counter is a L^AT_EX counter and incremented for each shipout attempt including those pages that are discarded for one or the other reason. Again `shipout/before` sees the counter before it is incremented. In contrast `shipout/after` sees the incremented value.

Furthermore, while it is incremented for each page, its value is never used by L^AT_EX. It can therefore be freely reset or changed by user code, for example, to additionally count a number of pages that are not build by L^AT_EX but are added in a later part of the process, e.g., cover pages or picture pages made externally.

Important: as this is a page-related counter its value is only reliable inside the output routine!

```
\PreviousTotalPages
```

```
\thetotalpages/\PreviousTotalPages
```

Command that expands to the number of total pages from the previous run. If there was no previous run or if used in the preamble it expands to 0. Note that this is a command and not a counter, so in order to display the number in, say, Roman numerals you have to assign its value to a counter and then use `\Roman` on that counter.

1.7 Debugging shipout code

```
\DebugShipoutsOn  
\DebugShipoutsOff  
\shipout_DEBUG_on:  
\shipout_DEBUG_off:
```

```
\DebugShipoutsOn
```

Turn the debugging of shipout code on or off. This displays changes made to the shipout data structures.

Todo: This needs some rationalizing and may not stay this way.

2 Emulating commands from other packages

The packages in this section are no longer necessary, but as they are used by other packages, they are emulated when they are explicitly loaded with `\usepackage` or `\RequirePackage`.

Please note that the emulation only happens if the package is explicitly requested, i.e., the commands documented below are not automatically available in the L^AT_EX kernel! If you write a new package we suggest to use the appropriate kernel hooks directly instead of loading the emulation.

2.1 Emulating `atbegshi`

<code>\AtBeginShipoutUpperLeft</code>	<code>\AddToHook {shipout/before}</code>
<code>\AtBeginShipoutUpperLeftForeground</code>	<code>{... \AtBeginShipoutUpperLeft{\langle code\rangle} ...}</code>

This adds a `picture` environment into the background of the shipout box expecting `\langle code\rangle` to contain `picture` commands. The same effect can be obtained by simply using kernel features as follows:

```
\AddToHook{shipout/background}{\langle code\rangle}
```

There is one technical difference: if `\AtBeginShipoutUpperLeft` is used several times each invocation is put into its own box inside the shipout box whereas all `\langle code\rangle` going into `shipout/background` ends up all in the same box in the order it is added or sorted based on the rules for the hook chunks.

`\AtBeginShipoutUpperLeftForeground` is similar with the difference that the `picture` environment is placed in the foreground. To model it with the kernel functions use the hook `shipout/foreground` instead.

<code>\AtBeginShipoutAddToBox</code>	<code>\AddToHook {shipout/before} {... \AtBeginShipoutAddToBox{\langle code\rangle} ...}</code>
<code>\AtBeginShipoutAddToBoxForeground</code>	

These work like `\AtBeginShipoutUpperLeft` and `\AtBeginShipoutUpperLeftForeground` with the difference that `\langle code\rangle` is directly placed into an `\hbox` inside the shipout box and not surrounded by a `picture` environment.

To emulate them using `shipout/background` or `shipout/foreground` you may have to wrap `\langle code\rangle` into a `\put` statement but if the code is not doing any typesetting just adding it to the hook should be sufficient.

<code>\AtBeginShipoutBox</code>	This is the name of the shipout box as <code>atbegshi</code> knows it.
---------------------------------	--

<code>\AtBeginShipoutOriginalShipout</code>	
---	--

This is the name of the `\shipout` primitive as `atbegshi` knows it. This bypasses all the mechanisms set up by the L^AT_EX kernel and there are various scenarios in which it can therefore fail. It should only be used to run existing legacy `atbegshi` code but not in newly developed applications.

The kernel alternative is `\RawShipout` which is integrated with the L^AT_EX mechanisms and updates, for example, the `\ ReadonlyShipoutCounter` counter. Please use `\RawShipout` for new code if you want to bypass the before, foreground and background hooks.

\AtBeginShipoutInit

By default `atbegshi` delayed its action until `\begin{document}`. This command was forcing it in an earlier place. With the new concept it does nothing.

**\AtBeginShipout
\AtBeginShipoutNext**

```
\AtBeginShipout{\code} \equiv \AddToHook{shipout/before}{\code}  
\AtBeginShipoutNext{\code} \equiv \AddToHookNext{shipout/before}{\code}
```

This is equivalent to filling the `shipout/before` hook by either using `\AddToHook` or `\AddToHookNext`, respectively.

**\AtBeginShipoutFirst
\AtBeginShipoutDiscard**

The `atbegshi` names for `\AtBeginDvi` and `\DiscardShipoutBox`.

2.2 Emulating `everyshi`

The `everyshi` package is providing commands to run arbitrary code just before the shipout starts. One point of difference: in the new shipout hooks the page is available as `\ShipoutBox` for inspection of change, one should not manipulate box 255 directly inside `shipout/before`, so old code doing this would change to use `\ShipoutBox` instead of 255 or `@cclv`.

\EveryShipout

```
\EveryShipout{\code} \equiv \AddToHook{shipout/before}{\code}
```

\AtNextShipout

```
\AtNextShipout{\code} \equiv \AddToHookNext{shipout/before}{\code}
```

However, most use cases for `everyshi` are attempts to put some picture or text into the background or foreground of the page and that can be done today simply by using the `shipout/background` and `shipout/foreground` hooks without any need to coding.

2.3 Emulating `atenddvi`

The `atenddvi` package implemented only a single command: `\AtEndDvi` and that is now available out of the box so the emulation makes the package a no-op.

2.4 Emulating `everypage`

This package patched the original `\@begindvi` hook and replaced it with its own version. Its functionality is now covered by the hooks offered by the kernel so that there is no need for such patching any longer.

\AddEverypageHook

```
\AddEverypageHook{\code} \equiv  
    \AddToHook{shipout/background}{\put(1in,-1in){\code}}
```

`\AddEverypageHook` is adding something into the background of every page at a position of 1in to the right and 1in down from the top left corner of the page. By using the kernel hook directly you can put your material directly to the right place, i.e., use other coordinates in the `\put` statement above.

\AddThispageHook

```
\AddThispageHook{\code} \equiv  
    \AddToHookNext{shipout/background}{\put(1in,-1in){\code}}
```

The `\AddThispageHook` wrapper is similar but uses `\AddToHookNext`.

3 The Implementation

```
1 <@@=shipout>
```

At the moment the whole module rolls back in one go, but if we make any modifications in later releases this will then need splitting.

```
2 <*2ekernel | latexrelease>
3 <latexrelease>\IncludeInRelease{2020/10/01}%
4 <latexrelease>          {\shipout}{Hook management (shipout)}%
5 \ExplSyntaxOn
```

3.1 Debugging

\g__shipout_debug_bool Holds the current debugging state.

```
6 \bool_new:N \g__shipout_debug_bool
```

(End definition for \g__shipout_debug_bool.)

```
\shipout_debug_on: Turns debugging on and off by redefining \__shipout_debug:n.
\shipout_debug_off:
\__shipout_debug:n
\__shipout_debug_gset:
```

7 \cs_new_eq:NN __shipout_debug:n \use_none:n
8 \cs_new_protected:Npn \shipout_debug_on:
9 {
10 \bool_gset_true:N \g__shipout_debug_bool
11 __shipout_debug_gset:
12 }
13 \cs_new_protected:Npn \shipout_debug_off:
14 {
15 \bool_gset_false:N \g__shipout_debug_bool
16 __shipout_debug_gset:
17 }
18 \cs_new_protected:Npn __shipout_debug_gset:
19 {
20 \cs_gset_protected:Npx __shipout_debug:n ##1
21 { \bool_if:NT \g__shipout_debug_bool {##1} }
22 }

(End definition for \shipout_debug_on: and others. These functions are documented on page 6.)

\ShipoutBox The box filled with the page to be shipped out (both L3 and L^AT_EX 2_E name).
\l_shipout_box

```
23 \box_new:N \l_shipout_box
```

```
24 \cs_set_eq:NN \ShipoutBox \l_shipout_box
```

(End definition for \ShipoutBox and \l_shipout_box. These functions are documented on page 2.)

\l__shipout_raw_box The \RawShipout gets its own box but it is internal as there is no hook manipulation for it.

```
25 \box_new:N \l__shipout_raw_box
```

(End definition for \l__shipout_raw_box.)

__shipout_finalize_box: For LuaTeX invoke the `pre_shipout_filter` callback.

```
26 \sys_if_engine_luatex:TF
27 {
28     \newluafunction \_\_shipout_finalize_box:
29     \exp_args:Nx \everyjob {
30         \exp_not:V \everyjob
31         \exp_not:N \lua_now:n {
32             luatexbase.create_callback('pre_shipout_filter', 'list')
33             local~call, getbox, setbox = luatexbase.call_callback, tex.getbox, tex.setbox~
34             lua.get_functions_table()[\the \_\_shipout_finalize_box:] = function()
35                 local~result = call('pre_shipout_filter', getbox(\the \l_shipout_box))
36                 if~not (result == true) then~
37                     setbox(\the \l_shipout_box, result~or~nil)
38                 end~
39             end
40         }
41     }
42     \protected \luadef \_\_shipout_finalize_box: \the \_\_shipout_finalize_box:
43 } {
44     \cs_set_eq:NN \_\_shipout_finalize_box: \scan_stop:
45 }
```

(End definition for `__shipout_finalize_box`.)

__shipout_execute: This is going to be the code run by `\shipout`. The code follows closely the ideas from atbegshi, so not documenting that here for now.

```
46 \cs_set_protected:Npn \_\_shipout_execute: {
47     \tl_set:Nx \l_\_\_shipout_group_level_tl
48     { \int_value:w \tex_currentgrouplevel:D }
49     \tex_afterassignment:D \_\_shipout_execute_test_level:
50     \tex_setbox:D \l_\_\_shipout_box
51 }
```

(End definition for `__shipout_execute`.)

\shipout Overloading the `\shipout` primitive:

```
52 \cs_gset_eq:NN \shipout \_\_shipout_execute:
```

(End definition for `\shipout`. This function is documented on page 2.)

\l___shipout_group_level_tl Helper token list to record the group level at which `__shipout_execute:` is encountered.

```
53 \tl_new:N \l_\_\_shipout_group_level_tl
```

(End definition for `\l___shipout_group_level_tl`.)

__shipout_execute_test_level: If the group level has changed then we are still constructing `\l___shipout_box` and to continue we need to wait until the current group has finished, hence the `\tex_aftergroup:D`.

```
54 \cs_new:Npn \_\_shipout_execute_test_level: {
55     \int_compare:nNnT
56     \l_\_\_shipout_group_level_tl < \tex_currentgrouplevel:D
57     \tex_aftergroup:D \_\_shipout_execute_cont:
58 }
```

(End definition for `__shipout_execute_test_level`.)

__shipout_execute_cont: This does the actual shipout running several hooks as part of it. The code for them is passed as argument #2 to #4 to __shipout_execute_main_cont:Nnnn; the first argument is the box to be shipped out.

```

59  \cs_new:Npn \_\_shipout_execute_cont: {
60    \_\_shipout_execute_main_cont:Nnnn
61      \l_shipout_box
62      { \hook_use:n {shipout/before} }
63      { \hook_if_empty:nF {shipout/foreground}
64        { \_\_shipout_add_foreground_picture:n
65          { \hook_use:n {shipout/foreground} } } }

```

If the user hook for the background (shipout/background) has no code, there might still code in the kernel hook so we need to test for this too. We only test for the @kernel@before@shipout@background though. If the @kernel@after@shipout@background needs executing even if the user hook is empty then we can add another test (or the kernel could put something into the before hook).

```

66      \bool_lazy_and:nnF
67      { \hook_if_empty_p:n {shipout/background} }
68      { \tl_if_empty_p:N @kernel@before@shipout@background }
69      { \_\_shipout_add_background_picture:n
70        { \@kernel@before@shipout@background
71          \hook_use:n {shipout/background}
72          \@kernel@after@shipout@background } }
73      }
74    }
75    { \hook_use:n {shipout/after} }
76  }

```

(End definition for __shipout_execute_cont:.)

__shipout_execute_main_cont:Nnnn When we have reached this point the shipout box has been processed and is available in \l_shipout_box and ready for real ship out (unless it gets discarded during the process). The three arguments hold hook code that is executed just before the actual shipout (#1), within the shipout adding background and foreground material (#2) and after the shipout has happened (#3). These are passed as arguments because the same code without those hooks is also used when doing a “raw” shipout implemented by \RawShipout. The only hook that is always executed is that for the very last page, i.e., shipout/lastpage.

First we quickly check if it is void (can’t happen in the standard L^AT_EX output routine but \shipout might be called from a package that has some special processing logic). If it is void we aren’t shipping anything out and processing ends.⁵

```

77  \cs_new:Npn \_\_shipout_execute_main_cont:Nnnn #1#2#3#4 {
78    \box_if_empty:NTF #1
79    { \@latex@warning@no@line{ Ignoring~ void~ shipout~ box } }
80    {

```

Otherwise we assume that we will ship something and prepare for final adjustments (in particular setting the state of \protect while we are running the hook code). We also save the current \protect state to restore it later.

```

81  %     \bool_gset_false:N \g__shipout_discard_bool  % setting this would disable
82                                % \DiscardShipoutBox on doc-level

```

⁵In that case we don’t reset the deadcycles, that would be up to the OR processing logic to do.

```

83      \cs_set_eq:NN \__shipout_saved_protect: \protect
84      \set@typeset@protect

```

We also store the current shipout box dimension in registers, so that they can be used in the hook code.⁶

```

85      \__shipout_get_box_size:N #1

```

Then we execute the `shipout/before` hook (or nothing in case of `\RawShipout`).

```

86      #2

```

In `\g_shipout_totalpages_int` we count all shipout attempts so we increment that counter already here (the other one is incremented later when we know for sure that we do a `\shipout`).

We increment it after running the above hook so that the values for `\g_shipout_totalpages_int` and `\g_shipout_READONLY_int` are in sync while the hook is executed (in the case that `totalpages` isn't manually altered or through discarding pages that is).

```

87      \int_gincr:N \g_shipout_totalpages_int

```

The above hook might contain code that requests the page to be discarded so we now test for it.

```

88      \bool_if:NTF \g__shipout_discard_bool
89      { \@latex@info@no@line{Completed- page~ discarded}
90      \bool_gset_false:N \g__shipout_discard_bool

```

As we are discarding the page box and not shipping anything out, we need to do some house cleaning and reset TeX's deadcycles so that it doesn't complain about too many calls to the OR without any shipout.

```

91      \tex_deadcycles:D \c_zero_int

```

Todo: In atbegshi the box was dropped but is that actually needed? Or the resetting of `\protect` to its kernel value?

```

92 %
93 %      \group_begin:
94 %      \box_set_eq_drop:NN #1 #1
95 %      \group_end:
96 %      \cs_set_eq:NN \protect \exp_not:N
         }

```

Even if there was no explicit request to discard the box it is possible that the code for the hook `shipout/before` has voided the box (by mistake or deliberately). We therefore test once more but this time make it a warning, because the best practice way is to use the request mechanism.

```

97      { \box_if_empty:NTF #1
98      { \@latex@warning@no@line { Ignoring~ void~ shipout~ box.
99      \MessageBreak The~ shipout~ box~ was~ voided~ by~ hook~ code }
100     }

```

Finally, if the box is still non-empty we are nearly ready to ship it out. First we increment the total page counter so that we can later test if we have reached the final page according to our available information.⁷

```

101     {

```

⁶This is not really necessary as the code could access them via `\box_ht:N`, etc., but it is perhaps convenient.

⁷Doing that earlier would be wrong because we might end up with the last page counted but discard and then we have no place to add the final objects into the output file.

```

102     \int_gincr:N \g_shipout_READONLY_int
103     \__shipout_debug:n {
104         \typeout{Absolute~ page~ =~ \int_use:N \g_shipout_READONLY_int
105             \space (target:~ \@abspage@last)}
106     }

```

Then we store the box sizes again (as they may have changed) and then look at the hooks `shipout/foreground` and `shipout/background`. If either or both are non-empty we add a `picture` environment to the box (in the foreground and/or in the background) and execute the hook code inside that environment.

```

107     \__shipout_get_box_size:N #1

```

The first hook we run is the `shipout/firstpage` hook. This is only done once, then the `__shipout_run_firstpage_hook:` command redefines itself to do nothing. If the hook contains `\specials` for integration at the top of the page they will be temporarily stored in a safe place and added later with `__shipout_add_firstpage_specials:`

```

108     \__shipout_run_firstpage_hook:

```

Run the hooks for background and foreground or, if this is called by `\RawShipout`, copy the box `\l__shipout_raw_box` to `\l_shipout_box` so that `firstpage` and `lastpage` material gets added if necessary (that is always done to `\l_shipout_box`).

```

109     #3

```

We then run `__shipout_add_firstpage_specials:` that adds the content of the hook `shipout/firstpage` to the start of the first page (if non-empty). It is then redefined to do nothing on later pages.

```

110     \__shipout_add_firstpage_specials:

```

Then we check if we have to add the `shipout/lastpage` hook or the corresponding kernel hook because we have reached the last page. This test will be false for all but one (and hopefully the correct) page.

```

111     \int_compare:nNnT \@abspage@last = \g_shipout_READONLY_int
112     { \bool_lazy_and:nnF
113         { \hook_if_empty_p:n {shipout/lastpage} }
114         { \tl_if_empty_p:N \@kernel@after@shipout@lastpage }
115     } \__shipout_debug:n { \typeout{Executing~ lastpage~ hook~
116         on~ page~ \int_use:N \g_shipout_READONLY_int } }
117     \__shipout_add_foreground_box:n
118     { \UseHook{shipout/lastpage}
119         \@kernel@after@shipout@lastpage
120     }
121     \bool_gset_true:N \g__shipout_lastpage_handled_bool
122     }
123     \__shipout_finalize_box:

```

Finally we run the actual TeX primitive for shipout. As that will expand delayed `\write` statements inside the page in which protected commands should not expand we first change `\protect` to the appropriate definition for that case.

```

124     \cs_set_eq:NN \protect \exp_not:N
125     \tex_shipout:D \box_use:N \l_shipout_box

```

The `\l_shipout_box` may contain the `firstpage` material if this was the very first shipout. That makes it unsuitable for reuse in another shipout, so as a safety measure the next command resets `\l_shipout_box` to its earlier state if that is necessary. On later pages this is then a no-op.

```

126     \__shipout_drop_firstpage_specials:

```

The `\shipout/after` hook (if in #4) needs to run with `\protected` commands again being executed, because that hook will “typeset” material added at the top of the next page.

```

127          \set@typeset@protect
128          #4
129      }
130  }
```

Restore the value of `\protect` in case `\shipout` is called outside of the output routine (where it is automatically restored because of the implicit group).

```

131          \cs_set_eq:NN \protect \__shipout_saved_protect:
132      }
133  }
```

(End definition for `__shipout_execute_main_cont:Nnnn`.)

`__shipout_execute_raw:` This implements the “raw” shipout which bypasses the before, foreground, background and after hooks. It follows the same pattern than `__shipout_execute_raw:` except that it finally calls `__shipout_execute_main_cont:Nnnn` with three empty arguments. instead of the hook code.

```

134 \cs_set_protected:Npn \__shipout_execute_raw: {
135   \tl_set:Nx \l__shipout_group_level_tl
136   { \int_value:w \tex_currentgrouplevel:D }
137   \tex_afterassignment:D \__shipout_execute_test_level_raw:
138   \tex_setbox:D \l__shipout_raw_box
139 }
140 \cs_new:Npn \__shipout_execute_test_level_raw: {
141   \int_compare:nNnT
142     \l__shipout_group_level_tl < \tex_currentgrouplevel:D
143     \tex_aftergroup:D \__shipout_execute_nohooks_cont:
144 }
```

Well, not totally empty arguments, we add some debugging if we are actually doing a shipout.

```

145 \cs_new:Npn \__shipout_execute_nohooks_cont: {
146   \__shipout_execute_main_cont:Nnnn \l__shipout_raw_box
147   {} { \__shipout_debug:n{ \typeout{Doing~ raw~ shipout~ ...} }
148     \box_set_eq:NN \l_shipout_box \l__shipout_raw_box } {}
149 }
```

(End definition for `__shipout_execute_raw:` and `__shipout_execute_test_level_raw:..`)

\RawShipout The interface name for raw shipout.

```
150 \cs_gset_eq:NN \RawShipout \__shipout_execute_raw:
```

(End definition for `\RawShipout`. This function is documented on page 2.)

`__shipout_saved_protect:` Remember the current `\protect` state.

```
151 \cs_new_eq:NN \__shipout_saved_protect: \protect
```

(End definition for `__shipout_saved_protect:..`)

```

shipout/before Declaring all hooks for the shipout code.
shipout/after
shipout/foreground
shipout/background
shipout/firstpage
shipout/lastpage
152 \hook_new:n{shipout/before}
153 \hook_new:n{shipout/after}
154 \hook_new:n{shipout/foreground}
155 \hook_new:n{shipout/background}
156 \hook_new:n{shipout/firstpage}
157 \hook_new:n{shipout/lastpage}

```

(End definition for `shipout/before` and others. These functions are documented on page 3.)

And here are the internal kernel hooks going before or after the public ones where needed.

```

\@kernel@after@shipout@lastpage
\@kernel@before@shipout@background
\@kernel@after@shipout@background
158 \let\@kernel@after@shipout@lastpage\@empty
159 \let\@kernel@before@shipout@background\@empty
160 \let\@kernel@after@shipout@background\@empty

```

(End definition for `\@kernel@after@shipout@lastpage`, `\@kernel@before@shipout@background`, and `\@kernel@after@shipout@background`. These functions are documented on page ??.)

`_shipout_run_firstpage_hook:` There are three commands to handle the `shipout/firstpage` hook: `_shipout_run_firstpage_hook:`, `_shipout_add_firstpage_specials:` and `_shipout_drop_firstpage_specials:`.

That hook is supposed to contain `\specials` and similar material to be placed at the very beginning of the output page and so it needs careful placing to avoid that anything else gets in front of it. And this means we have to wait with this until other hooks such as `shipout/background` have added their bits. It is also important that such `\specials` show up only on the very first page, so if this page gets saved before `\shipout` for later reuse, we have to make sure that they aren't in the saved version.

In addition the hook may also contain code to be executed "first", e.g., visible from code in `shipout/background` and this conflicts with adding the `\specials` late.

Therefore the processing is split into different parts: `_shipout_run_firstpage_hook:` is done early and checks if there is any material in the hook.

```

161 \cs_new:Npn \_shipout_run_firstpage_hook: {
162   \hook_if_empty:nTF {shipout/firstpage}

```

If not then we define the other two commands to do nothing.

```

163   {
164     \cs_gset_eq:NN \_shipout_add_firstpage_specials: \prg_do_nothing:
165     \cs_gset_eq:NN \_shipout_drop_firstpage_specials: \prg_do_nothing:
166   }

```

If there is material we execute inside a box, which means any `\special` will end up in that box and any other code is executed and can have side effects (as long as they are global).

```

167   {
168     \hbox_set:Nn \l__shipout_firstpage_box { \UseHook{shipout/firstpage} }
169   }

```

Once we are here we change the definition to do nothing next time and we also change the command used to implement `\AtBeginDvi` to become a warning and not add further material to a hook that is never used again.

```

170   \cs_gset_eq:NN \_shipout_run_firstpage_hook: \prg_do_nothing:
171   \cs_gset:Npn \_shipout_add_firstpage_material:Nn ##1 ##2 {
172     \o@lateX@warning{ First~ page~ is~ already~ shipped~ out,~ ignoring

```

```

173           \MessageBreak \string##1 }
174     }
175 }
```

(End definition for `__shipout_run_firstpage_hook`.)

`__shipout_add_firstpage_specials:`
`__shipout_drop_firstpage_specials:`

The `__shipout_add_firstpage_specials`: then adds the `\specials` stored in `\l__shipout_firstpage_box` to the page to be shipped out when the time is ready. Note that if there was no material in the `shipout/firstpage` hook then this command gets redefined to do nothing. But for most documents there is something, e.g., some PostScript header, or some meta data declaration, etc. so by default we assume there is something to do.

```
176 \cs_new:Npn \__shipout_add_firstpage_specials: {
```

First we make a copy of the `\l_shipout_box` that we can restore it later on.

```
177   \box_set_eq:NN \l__shipout_raw_box \l_shipout_box
```

Adding something to the beginning means adding it to the background as that layer is done first in the output.

```
178   \__shipout_add_background_box:n { \hbox_unpack_drop:N \l__shipout_firstpage_box }
```

After the actual shipout `__shipout_drop_firstpage_specials`: is run to restore the earlier content of `\l_shipout_box` and then redefines itself again to do nothing.

As a final act we change the definition to do nothing next time.

```
179 \cs_gset_eq:NN \__shipout_add_firstpage_specials: \prg_do_nothing:
180 }
```

The `__shipout_drop_firstpage_specials`: is run after the shipout has occurred but before the `shipout/afterpage` hook is executed. That is the point where we have to restore the `\ShipoutBox` to its state without the `shipout/firstpage` material.

```
181 \cs_new:Npn \__shipout_drop_firstpage_specials: {
182   \box_set_eq:NN \l_shipout_box \l__shipout_raw_box
```

If there was no such material then `__shipout_run_firstpage_hook`: will have changed the definition to a no-op already. Otherwise this is what we do here.

```
183   \cs_gset_eq:NN \__shipout_drop_firstpage_specials: \prg_do_nothing:
184 }
```

(End definition for `__shipout_add_firstpage_specials`: and `__shipout_drop_firstpage_specials`.)

`\l__shipout_firstpage_box`

The box to hold any firstpage `\specials`.

```
185 \box_new:N \l__shipout_firstpage_box
```

(End definition for `\l__shipout_firstpage_box`.)

`\g__shipout_lastpage_handled_bool`

A boolean to signal if we have already handled the `shipout/lastpage` hook.

```
186 \bool_new:N \g__shipout_lastpage_handled_bool
```

(End definition for `\g__shipout_lastpage_handled_bool`.)

`__shipout_add_firstpage_material:Nn`

This command adds material to the `shipout/firstpage` hook. It is used in `\AtBeginDvi`, etc. The first argument is the command through which is it called. Initially this is ignored but once we are passed the first page it can be used to generate a warning message mentioning the right user command.

```
187 \cs_new:Npn \__shipout_add_firstpage_material:Nn #1#2 {
188   \AddToHook{shipout/firstpage}{#2}
189 }
```

(End definition for `__shipout_add_firstpage_material:Nn`.)

`__shipout_get_box_size:N` Store the box dimensions in dimen registers.

Todo: This could/should perhaps be generalized to set height depth and width given an arbitrary box.

```
190 \cs_new:Npn \__shipout_get_box_size:N #1 {
191     \dim_set:Nn \l_shipout_box_ht_dim { \box_ht:N #1 }
192     \dim_set:Nn \l_shipout_box_dp_dim { \box_dp:N #1 }
193     \dim_set:Nn \l_shipout_box_wd_dim { \box_wd:N #1 }
194     \dim_set:Nn \l_shipout_box_ht_plus_dp_dim
195         { \l_shipout_box_ht_dim + \l_shipout_box_dp_dim }
196 }
```

(End definition for `__shipout_get_box_size:N`.)

`\l_shipout_box_ht_dim` And here are the variables set by `__shipout_get_box_size:N`.

```
197 \dim_new:N \l_shipout_box_ht_dim
198 \dim_new:N \l_shipout_box_dp_dim
199 \dim_new:N \l_shipout_box_wd_dim
200 \dim_new:N \l_shipout_box_ht_plus_dp_dim
```

(End definition for `\l_shipout_box_ht_dim` and others. These functions are documented on page 3.)

`\g__shipout_discard_bool` Indicate whether or not the current page box should be discarded

```
201 \bool_new:N \g__shipout_discard_bool
```

(End definition for `\g__shipout_discard_bool`.)

`\l__shipout_tmp_box` We need a box for the background and foreground material and a token register to remember badness settings as we disable them during the buildup below.

```
202 \box_new:N \l__shipout_tmp_box
203 \tl_new:N \l__shipout_saved_badness_tl
```

(End definition for `\l__shipout_tmp_box` and `\l__shipout_saved_badness_tl`.)

`__shipout_add_background_box:n` In standard L^AT_EX the shipout box is always a `\vbox` but here we are allow for other usage as well, in case some package has its own output routine.

```
204 \cs_new:Npn \__shipout_add_background_box:n #1
205 { \__shipout_get_box_size:N \l_shipout_box
```

But we start testing for a vertical box as that should be the normal case.

```
206 \box_if_vertical:NTF \l_shipout_box
207 {
```

Save current values of `\vfuzz` and `\vbadness` then change them to allow box manipulations without warnings.

```
208 \tl_set:Nx \l__shipout_saved_badness_tl
209 { \vfuzz=\the\vfuzz\relax
210     \vbadness=\the\vbadness\relax }
211 \vfuzz=\c_max_dim
212 \vbadness=\c_max_int
```

Then we reconstruct `\l_shipout_box` ...

```
213 \vbox_set_to_ht:Nnn \l_shipout_box \l_shipout_box_ht_plus_dp_dim
214 {
```

... the material in #1 is placed into a horizontal box with zero dimensions.

```

215          \hbox_set:Nn \l_shipout_tmp_box
216              { \l_shipout_saved_badness_t1 #1 }
217          \box_set_wd:Nn \l_shipout_tmp_box \c_zero_dim
218          \box_set_ht:Nn \l_shipout_tmp_box \c_zero_dim
219          \box_set_dp:Nn \l_shipout_tmp_box \c_zero_dim

```

The we typeset that box followed by whatever was in \l_shipout_box before (unpacked).

```

220          \skip_zero:N \baselineskip
221          \skip_zero:N \lineskip
222          \skip_zero:N \lineskiplimit
223          \box_use:N \l_shipout_tmp_box
224          \vbox_unpack:N \l_shipout_box

```

The \kern ensures that the box has no depth which is afterwards explicitly corrected.

```

225          \kern \c_zero_dim
226      }
227      \box_set_ht:Nn \l_shipout_box \l_shipout_box_ht_dim
228      \box_set_dp:Nn \l_shipout_box \l_shipout_box_dp_dim

```

Todo: The whole boxing maneuver looks a bit like overkill to me, but for the moment I leave.

```

229          \l_shipout_saved_badness_t1
230      }
231  {

```

A horizontal box is handled in a similar way. The last case would be a void box in which case we do nothing hence the missing F branch.

```

232          \box_if_horizontal:NT \l_shipout_box
233      {
234          \tl_set:Nx \l_shipout_saved_badness_t1
235              { \hfuzz=\the\hfuzz\relax
236                  \hbadness=\the\hbadness\relax }
237          \hfuzz=\c_max_dim
238          \hbadness=\c_max_int
239          \hbox_set_to_wd:Nnn \l_shipout_box \l_shipout_box_wd_dim
240      {
241          \hbox_set:Nn \l_shipout_tmp_box
242              { \l_shipout_saved_badness_t1 #1 }
243          \box_set_wd:Nn \l_shipout_tmp_box \c_zero_dim
244          \box_set_ht:Nn \l_shipout_tmp_box \c_zero_dim
245          \box_set_dp:Nn \l_shipout_tmp_box \c_zero_dim
246          \box_move_up:nn
247              \l_shipout_box_ht_dim
248              { \box_use:N \l_shipout_tmp_box }
249          \hbox_unpack:N \l_shipout_box
250      }
251      \l_shipout_saved_badness_t1
252  }
253 }
254

```

(End definition for __shipout_add_background_box:n.)

_shipout_add_foreground_box:n Foreground boxes are done in the same way, only the order and placement of boxes has to be done differently.

```
255 \cs_new:Npn \_shipout_add_foreground_box:n #1
256 {
257     \box_if_vertical:NTF \l_shipout_box
258     {
259         \tl_set:Nx \l__shipout_saved_badness_tl
260         { \vfuzz=\the\vfuzz\relax
261             \vbadness=\the\vbadness\relax }
262         \vfuzz=\c_max_dim
263         \vbadness=\c_max_int
264         \vbox_set_to_ht:Nnn \l_shipout_box \l_shipout_box_ht_plus_dp_dim
265         {
266             \hbox_set:Nn \l__shipout_tmp_box
267             { \l__shipout_saved_badness_tl #1 }
268             \box_set_wd:Nn \l__shipout_tmp_box \c_zero_dim
269             \box_set_ht:Nn \l__shipout_tmp_box \c_zero_dim
270             \box_set_dp:Nn \l__shipout_tmp_box \c_zero_dim
271             \skip_zero:N \baselineskip
272             \skip_zero:N \lineskip
273             \skip_zero:N \lineskiplimit
274             \vbox_unpack:N \l_shipout_box
275             \kern -\l_shipout_box_ht_plus_dp_dim
276             \box_use:N \l__shipout_tmp_box
277             \kern \l_shipout_box_ht_plus_dp_dim
278         }
279         \l__shipout_saved_badness_tl
280         \box_set_ht:Nn \l_shipout_box \l_shipout_box_ht_dim
281         \box_set_dp:Nn \l_shipout_box \l_shipout_box_dp_dim
282     }
283     {
284         \box_if_horizontal:NT \l_shipout_box
285         {
286             \tl_set:Nx \l__shipout_saved_badness_tl
287             { \hfuzz=\the\hfuzz\relax
288                 \hbadness=\the\hbadness\relax }
289             \hfuzz=\c_max_dim
290             \hbadness=\c_max_int
291             \hbox_set_to_wd:Nnn \l_shipout_box \l_shipout_box_wd_dim
292             {
293                 \hbox_unpack:N \l_shipout_box
294                 \kern -\box_wd:N \l_shipout_box
295                 \hbox_set:Nn \l__shipout_tmp_box
296                 { \l__shipout_saved_badness_tl #1 }
297                 \box_set_wd:Nn \l__shipout_tmp_box \c_zero_dim
298                 \box_set_ht:Nn \l__shipout_tmp_box \c_zero_dim
299                 \box_set_dp:Nn \l__shipout_tmp_box \c_zero_dim
300                 \box_move_up:nn { \box_ht:N \l_shipout_box }
301                 { \box_use:N \l__shipout_tmp_box }
302                 \kern \box_wd:N \l_shipout_box
303             }%
304             \l__shipout_saved_badness_tl
305         }
306     }
```

307 }

(End definition for `_shipout_add_foreground_box:n`.)

```
\_shipout_init_page_origins:  
\c__shipout_horigin_tl  
\c__shipout_vorigin_tl
```

Two constants holding the offset of the top-left with respect to the media box.

Setting the constants this way is courtesy of Bruno.

We delay setting the constants to the last possible place as there might be updates in the preamble or even in the `begindocument` hook that affects their setup.

```
308 \cs_new:Npn \_shipout_init_page_origins: {  
309   \tl_const:Nx \c__shipout_horigin_tl  
310   {  
311     \cs_if_exist_use:NTF \pdfvariable { horigin }  
312       { \cs_if_exist_use:NF \pdfhorigin { 1in } }  
313   }  
314   \tl_const:Nx \c__shipout_vorigin_tl  
315   {  
316     \cs_if_exist_use:NTF \pdfvariable { vorigin }  
317       { \cs_if_exist_use:NF \pdfvorigin { 1in } }  
318   }
```

After the constants have been set there is no need to execute this command again, in fact it would raise an error, so we redefine it to do nothing.

```
319   \cs_gset_eq:NN \_shipout_init_page_origins: \prg_do_nothing:  
320 }
```

(End definition for `_shipout_init_page_origins:`, `\c__shipout_horigin_tl`, and `\c__shipout_vorigin_tl`.)

```
\_shipout_picture_overlay:n
```

Put the argument into a `picture` environment that doesn't take up any size and uses `1pt` for `\unitlength`.

Todo: Could perhaps be generalized as it might be useful elsewhere. For now it is not.

```
321 \cs_new:Npn \_shipout_picture_overlay:n #1 {
```

The very first time this is executed we have to initialize (and freeze) the origins.

```
322   \_shipout_init_page_origins:  
323   \kern -\c__shipout_horigin_tl \scan_stop:  
324   \vbox_to_zero:n {  
325     \kern -\c__shipout_vorigin_tl \scan_stop:  
326     \unitlength 1pt \scan_stop:
```

This mimics a simple zero-sized picture environment. The `\hss` is need in case there is horizontal material (without using `\put` with a positive width).

```
327   \hbox_set_to_wd:Nnn \l__shipout_tmp_box \c_zero_dim  
328   { \ignorespaces #1 \hss }  
329   \box_set_ht:Nn \l__shipout_tmp_box \c_zero_dim  
330   \box_set_dp:Nn \l__shipout_tmp_box \c_zero_dim  
331   \box_use:N \l__shipout_tmp_box  
332   \tex_vss:D  
333 }  
334 }
```

(End definition for `_shipout_picture_overlay:n`.)

`_shipout_add_background_picture:n` Put a `picture` env in the background of the shipout box with its reference point in the top-left corner.

```
335 \cs_new:Npn \_shipout_add_background_picture:n #1 {
336     \_shipout_add_background_box:n { \_shipout_picture_overlay:n {#1} }
337 }
```

(*End definition for `_shipout_add_background_picture:n`.*)

`_shipout_add_foreground_picture:n` Put a `picture` env in the foreground of the shipout box with its reference point in the top-left corner.

```
338 \cs_new:Npn \_shipout_add_foreground_picture:n #1 {
339     \_shipout_add_foreground_box:n { \_shipout_picture_overlay:n {#1} }
340 }
```

(*End definition for `_shipout_add_foreground_picture:n`.*)

\shipout_discard: Request that the next shipout box should be discarded. At the moment this is just setting a boolean, but we may want to augment this behavior that the position of the call is taken into account (in case L^AT_EX looks ahead and is not using the position for on the next page).

```
341 \cs_new_protected:Npn \shipout_discard: {
342     \bool_gset_true:N \g__shipout_discard_bool
343 }
```

(*End definition for `\shipout_discard`:. This function is documented on page 5.*)

3.2 Handling the end of job hook

At the moment this is partly solved by using the existing hooks. But rather than putting the code into these hooks it should be moved to the right place directly as we shouldn't prefill hooks with material unless it needs to interact with other code.

\g_shipout_READONLY_int
\ ReadonlyShipoutCounter We count every shipout activity that makes a page (but not those that are discarded) in order to know how many pages got produced.

```
344 \int_new:N \g_shipout_READONLY_int
```

For L^AT_EX 2_E it is available as a command (i.e., a T_EX counter only).

```
345 \cs_new_eq:NN \ ReadonlyShipoutCounter \g_shipout_READONLY_int
```

(*End definition for `\g_shipout_READONLY_int` and `\ ReadonlyShipoutCounter`. These functions are documented on page 6.*)

\g_shipout_TOTALPAGES_int
\c@totalpages We count every shipout attempt (even those that are discarded) in this counter. It is not used in the code but may get used in user code.

```
346 \int_new:N \g_shipout_TOTALPAGES_int
```

For L^AT_EX 2_E this is offered as a L^AT_EX counter so can be easily typeset inside the output routine to display things like “`\thepage/\thetotalpages`”, etc.

```
347 \cs_new_eq:NN \c@totalpages \g_shipout_TOTALPAGES_int
348 \cs_new:Npn \thetotalpages { \arabic{totalpages} }
```

(*End definition for `\g_shipout_TOTALPAGES_int` and `\c@totalpages`. These functions are documented on page 6.*)

\@abspage@last In \@abspage@last record the number of pages from the last run. This is written to the .aux and this way made available to the next run. In case there is no .aux file or the statement is missing from it we initialize it with the largest possible number in TeX. We use this as the default because then we are inserting the `shipout/lastpage` on the last page (or after the last page) but not on page 1 for a multipage document.

```
349 \xdef\@abspage@last{\number\maxdimen}
```

(End definition for \@abspage@last. This function is documented on page ??.)

\enddocument Instead of using the hooks `enddocument` and `enddocument/afterlastpage` we add this code to private kernel hooks to be 100% sure when it is executed and to avoid cluttering the hooks with data that is always there.

Inside \enddocument there is a \clearpage. Just before that we execute this code here. There is a good chance that we are on the last page. Therefore, if we don't know the value from the last run, we assume that the current page is the right one. So we set \@abspage@last and as a result the next shipout will run the `shipout/lastpage` code. Of course, if there are floats that still need a placement this guess will be wrong but then rerunning the document will give us the correct value next time around.

\@kernel@after@enddocument

```
350 \g@addto@macro \@kernel@after@enddocument {
351   \int_compare:nNnT \@abspage@last = \maxdimen
352 }
```

We use L^AT_EX 2 _{ε} coding as \@abspage@last is not an L3 name.

```
353   \xdef\@abspage@last{ \int_eval:n {\g_shipout_READONLY_int + 1} }
354 }
355 }
```

Once the \clearpage has done its work inside \enddocument we know for sure how many pages this document has, so we record that in the .aux file for the next run.

```
356 \g@addto@macro \@kernel@after@enddocument@afterlastpage {
```

There is one special case: If no output is produced then there is no point in a) recording the number as 0 will never match the page number of a real page and b) adding an extra page to ran the `shipout/lastpage` is pointless as well (as it would remain forever). So we test for this and run the code only if there have been pages.

```
357   \int_compare:nNnF \g_shipout_READONLY_int = 0
358 }
```

This ends up in the .aux so we use L^AT_EX 2 _{ε} names here.

Todo: This needs an interface for \nofiles in expl3, doesn't at the moment!

```
359   \if@filesw
360     \iow_now:Nx \@auxout {
361       \gdef\string\@abspage@last {\int_use:N \g_shipout_READONLY_int}}
362   \fi
```

But we may have guessed wrongly earlier and we still have to run the `shipout/lastpage` even though there is no page to place it into. If that is the case we make a trivial extra page and put it there. This temporary page will then vanish again on the next run but helps to keep pdf viewers happy.

```
363   \bool_if:NF \g__shipout_lastpage_handled_bool
364 }
```

However, making this extra page in case the hook is actually empty would be forcing a rerun without any reason, so we check that condition and also check if `\@kernel@after@shipout@lastpage` contains any code. If both are empty we omit the page generation.

```

365      \bool_lazy_and:nnF
366      { \hook_if_empty_p:n {shipout/lastpage} }
367      { \tl_if_empty_p:N \@kernel@after@shipout@lastpage }
368      {
369          \tex_shipout:D\vbox to\textheight
370          {
371              \hbox:n { \UseHook{shipout/lastpage}
372                      \@kernel@after@shipout@lastpage }

```

This extra page could be totally empty except for the hook content, but to help the user understanding why it is there we put some text into it.

```

373      \__shipout_excuse_extra_page:
374      \null
375  }

```

At this point we also signal to L^AT_EX's endgame that a rerun is necessary so that an appropriate message can be shown on the terminal. We do this by simply defining a command used as a flag and tested in `\enddocument`.

```

376      \cs_gset_eq:NN \cextra@page@added \relax
377      }
378      }
379      }
380  }

```

(End definition for `\enddocument`, `\@kernel@after@enddocument`, and `\@kernel@after@enddocument@afterlastpage`. These functions are documented on page ??.)

`__shipout_excuse_extra_page:` Say mea culpa ...

```

381 \cs_new:Npn \__shipout_excuse_extra_page: {
382     \vfil
383     \begin{center}
384         \bfseries Temporary~ page!
385     \end{center}
386     \LaTeX{} was~ unable~ to~ guess~ the~ total~ number~ of~ pages~
387     correctly.~ ~ As~ there~ was~ some~ unprocessed~ data~ that~
388     should~ have~ been~ added~ to~ the~ final~ page~ this~ extra~
389     page~ has~ been~ added~ to~ receive~ it.
390     \par
391     If~ you~ rerun~ the~ document~ (without~ altering~ it)~ this~
392     surplus~ page~ will~ go~ away,~ because~ \LaTeX{} now~ knows~
393     how~ many~ pages~ to~ expect~ for~ this~ document.
394     \vfil
395 }

```

(End definition for `__shipout_excuse_extra_page:..`)

`\PreviousTotalPages` In the preamble before the aux file was read `\PreviousTotalPages` is always zero.
`\@kernel@before@begindocument`

```

396 \def\PreviousTotalPages{0}

```

In the aux file there should be an update for `\@abspage@last` recording the number of pages from the previous run. If not that macro holds the value of `\maxdimen`. So we test for it and update `\PreviousTotalPages` if there was a real value. This should happen just before the `begindocument` hook is executed so that the value can be used inside that hook.

```
397 \g@addto@macro\@kernel@before@begindocument
398 {\ifnum\@abspage@last<\maxdimen
399     \xdef\PreviousTotalPages{\@abspage@last}\fi}
```

(End definition for `\PreviousTotalPages` and `\@kernel@before@begindocument`. These functions are documented on page 6.)

4 Legacy L^AT_EX 2 _{ϵ} interfaces

`\DiscardShipoutBox` Request that the next shipout box is to be discarded.

```
400 \cs_new_eq:NN \DiscardShipoutBox \shipout_discard:
```

(End definition for `\DiscardShipoutBox`. This function is documented on page 5.)

`\AtBeginDvi` If we roll forward from an earlier kernel `\AtBeginDvi` is defined so we better not use `\cs_new_protected:Npn` here.

```
401 \cs_set_protected:Npn \AtBeginDvi
402     {\_shipout_add_firstpage_material:Nn \AtBeginDvi}
```

(End definition for `\AtBeginDvi`. This function is documented on page 4.)

`\DebugShipoutsOn`

`\DebugShipoutsOff`

```
403 \cs_new_eq:NN \DebugShipoutsOn \shipout_debug_on:
404 \cs_new_eq:NN \DebugShipoutsOff \shipout_debug_off:
```

(End definition for `\DebugShipoutsOn` and `\DebugShipoutsOff`. These functions are documented on page 6.)

5 Internal commands needed elsewhere

These internal commands use double and triple @ signs so we need to stop getting them translated to the module name.

```
405 <@@=
```

Some internals needed elsewhere.

```
406 \cs_set_eq:NN \@expl@@@shipout@add@firstpage@material@@Nn
407     \_shipout_add_firstpage_material:Nn
408 \cs_set_eq:NN \@expl@@@shipout@add@background@box@@n
409     \_shipout_add_background_box:n
410 \cs_set_eq:NN \@expl@@@shipout@add@foreground@box@@n
411     \_shipout_add_foreground_box:n
412 \cs_set_eq:NN \@expl@@@shipout@add@background@picture@@n
413     \_shipout_add_background_picture:n
414 \cs_set_eq:NN \@expl@@@shipout@add@foreground@picture@@n
415     \_shipout_add_foreground_picture:n
```

(End definition for \Expl@@@shipout@add@firstpage@material@Nn and others. These functions are documented on page ??.)

```
416 \ExplSyntaxOff
417 
```

```
418 \end{IncludeInRelease}
```

Rolling back here doesn't undefine the interface commands as they may be used in packages without rollback functionality. So we just make them do nothing which may or may not work depending on the code usage.

```
419 \end{IncludeInRelease}{0000/00/00}%
420 
```

```
421 \end{IncludeInRelease}
```

If we roll forward then \tex_shipout:D may not be defined in which case \shipout does have its original definition and so we must not \let it to something else which is \relax!

```
422 \ifcsname tex_shipout:D\endcsname
423 \expandafter\let\expandafter\shipout
424 \csname tex_shipout:D\endcsname
425 \fi
426 
```

```
427 \let \RawShipout\undefined
```

```
428 \let \ShipoutBox\undefined
```

```
429 \let \ReadonlyShipoutCounter \undefined
```

```
430 \let \c@totalpages \undefined
```

```
431 \let \thetotalpages \undefined
```

```
432 
```

```
433 \let \DiscardShipoutBox \undefined
```

```
434 \let \DebugShipoutsOn \undefined
```

```
435 \let \DebugShipoutsOff \undefined
```

```
436 
```

```
437 \DeclareRobustCommand \AtBeginDvi [1]{%
```

```
438 \global \setbox \begindvibox
```

```
439 \vbox{\unvbox \begindvibox #1}%
440 
```

```
441 
```

```
442 \let \AtBeginShipout \undefined
```

```
443 \let \AtBeginShipoutNext \undefined
```

```
444 
```

```
445 \let \AtBeginShipoutFirst \undefined
```

```
446 
```

```
447 \let \ShipoutBoxHeight \undefined
```

```
448 \let \ShipoutBoxDepth \undefined
```

```
449 \let \ShipoutBoxWidth \undefined
```

```
450 
```

We do not undo a substitution when rolling back. As the file support gets undone the underlying data is no longer used (and sufficiently obscure that it should not interfere with existing commands) and properly removing it would mean we need to make the \undeclare@... and its support macros available in all earlier kernel releases which is pointless (and actually worse).

```
451 
```

```
452 \let \AtEndDvi \undefined
```

We do not reenable a disabled package load when rolling back. As the file support gets undone the underlying data is no longer checked (and sufficiently obscure that it should not interfere with existing commands) and properly removing it would mean we need to make the `\reenable@package@load` command available in all earlier kernel releases which is pointless (and actually worse).

```
453  \%reenable@package@load{atenddvi}
454  <|latexrelease>
455  <|latexrelease>\EndIncludeInRelease
456  <*2ekernel>
```

6 Package emulation for compatibility

6.1 Package **atenddvi** emulation

\AtEndDvi This package has only one public command to simulating it is easy and actually sensible to provide as part of the kernel.

```
457  </2ekernel>
458  <*2ekernel | latexrelease>
459  <|latexrelease>\IncludeInRelease{2020/10/01}%
460  <|latexrelease>                      {\AtEndDvi}{atenddvi emulation}%
461  \ExplSyntaxOn
462  \cs_new_protected:Npn \AtEndDvi {\AddToHook{shipout/lastpage}}
463  \ExplSyntaxOff
```

As the package is integrate we prevent loading (no need to roll that back):

```
464  \disable@package@load{atenddvi}
465  {\PackageWarning{atenddvi}
466    {Functionality of this package is already\MessageBreak
467     provided by LaTeX.\MessageBreak\MessageBreak
468     It is there no longer necessary to load it.\MessageBreak
469     and you can safely remove it.\MessageBreak
470     Found on}}
471  </2ekernel | latexrelease>
472  <|latexrelease>\EndIncludeInRelease
473  <|latexrelease>\IncludeInRelease{0000/00/00}%
474  <|latexrelease>                      {\AtEndDvi}{atenddvi emulation}%
475  <|latexrelease>\let \AtEndDvi \undefined
476  <|latexrelease>\EndIncludeInRelease
477  <*2ekernel>
```

(*End definition for \AtEndDvi. This function is documented on page 4.*)

```
478  </2ekernel>
```

6.2 Package **atbegshi** emulation

```
479  <*atbegshi-ltx>
480  \ProvidesPackage{atbegshi-ltx}
481  [2021/01/10 v1.0c
482  Emulation of the original atbegshi^^Jpackage with kernel methods]
```

\AtBeginShipoutBox

```
483  \let \AtBeginShipoutBox \ShipoutBox
```

(End definition for `\AtBeginShipoutBox`. This function is documented on page 7.)

`\AtBeginShipoutInit` Compatibility only, we aren't delaying ...

484 `\let \AtBeginShipoutInit \empty`

(End definition for `\AtBeginShipoutInit`. This function is documented on page 8.)

`\AtBeginShipout` Filling hooks

`\AtBeginShipoutNext` 485 `\protected \def \AtBeginShipout {\AddToHook{shipout/before}}`
486 `\protected \def \AtBeginShipoutNext {\AddToHookNext{shipout/before}}`

(End definition for `\AtBeginShipout` and `\AtBeginShipoutNext`. These functions are documented on page 8.)

`\AtBeginShipoutFirst` Slightly more complex as we need to know the name of the command under which the `shipout/firstpage` hook is filled.

487 `\protected \def \AtBeginShipoutFirst {\Expl@@@shipout@add@firstpage@material@@Nn \AtBeginShipoutFirst}`

(End definition for `\AtBeginShipoutFirst`. This function is documented on page 8.)

`\AtBeginShipoutDiscard` Just a different name.

489 `\let \AtBeginShipoutDiscard \DiscardShipoutBox`

(End definition for `\AtBeginShipoutDiscard`. This function is documented on page 8.)

`\AtBeginShipoutAddToBox` We don't expose them.

490 `\let \AtBeginShipoutAddToBox`

`\Expl@@@shipout@add@background@box@@n`

`\AtBeginShipoutUpperLeft` 491 `\let \AtBeginShipoutAddToBoxForeground`

`\Expl@@@shipout@add@foreground@box@@n`

492 `\let \AtBeginShipoutUpperLeft`

`\Expl@@@shipout@add@background@picture@@n`

493 `\let \AtBeginShipoutUpperLeftForeground`

`\Expl@@@shipout@add@foreground@picture@@n`

(End definition for `\AtBeginShipoutAddToBox` and others. These functions are documented on page 7.)

`\AtBeginShipoutOriginalShipout`

This offers the raw `\shipout` primitive of the engine. A page shipped out with this is not counted by `\ ReadonlyShipoutCounter` counter and thus the mechanism to place `\specials` at the very end of the output might fail, etc. It should therefore not be used in new applications but is only provided to allow running legacy code. For new code use the commands provided by the kernel instead.

498 `\ExplSyntaxOn`

499 `\cs_new_eq:NN \AtBeginShipoutOriginalShipout \tex_shipout:D`

(End definition for `\AtBeginShipoutOriginalShipout`. This function is documented on page 7.)

`\ShipoutBoxHeight` This is somewhat different from the original in `atbegshi` where `\ShipoutBoxHeight` etc. only holds the `\the\ht<box>` value. This may have some implications in some use cases and if that is a problem then it might need changing.

500 `\cs_new:Npn \ShipoutBoxHeight { \dim_use:N \l_shipout_box_ht_dim }`

501 `\cs_new:Npn \ShipoutBoxDepth { \dim_use:N \l_shipout_box_dp_dim }`

502 `\cs_new:Npn \ShipoutBoxWidth { \dim_use:N \l_shipout_box_wd_dim }`

503 `\ExplSyntaxOff`

(End definition for `\ShipoutBoxHeight`, `\ShipoutBoxWidth`, and `\ShipoutBoxDepth`. These functions are documented on page ??.)

504 `</atbegshi-ltx>`

If the package is requested we substitute the one above:

```
505 <*2ekernel>
506 \declare@file@substitution{atbegshi.sty}{atbegshi-ltx.sty}
507 </2ekernel>
```

6.3 Package `everyshi` emulation

This is now directly handled in that package so emulation is not necessary any more.

Rather important :-)

508 `<@@=`

Index

The italic numbers denote the pages where the corresponding entry is described, numbers underlined point to the definition, all others indicate the places where it is used.

A	C
<code>\AddEverypageHook</code>	<code>\bool_lazy_and:nnTF</code> 66, 112, 365
<code>\AddThispageHook</code>	<code>\bool_new:N</code> 6, 186, 201
<code>\AddToHook</code> 6–8, 188, 462, 485	box commands:
<code>\AddToHookNext</code> 4, 7, 8, 486	<code>\box_dp:N</code> 192
<code>\Alph</code> 5	<code>\box_ht:N</code> 11, 191, 300
<code>\arabic</code> 5, 348	<code>\box_if_empty:NTF</code> 78, 97
<code>\AtBeginDvi</code> 4, 7, 15, 16, 23, 401, 437	<code>\box_if_horizontal:NTF</code> 232, 284
<code>\AtBeginShipout</code> 7, 442, 485	<code>\box_if_vertical:NTF</code> 206, 257
<code>\AtBeginShipoutAddToBox</code> 6, 490	<code>\box_move_up:nn</code> 246, 300
<code>\AtBeginShipoutAddToBoxForeground</code> 6, 490	<code>\box_new:N</code> 23, 25, 185, 202
<code>\AtBeginShipoutBox</code> 6, 483	<code>\box_set_dp:Nn</code> 219, 228, 245, 270, 281, 299, 330
<code>\AtBeginShipoutDiscard</code> 7, 489	<code>\box_set_eq:NN</code> 148, 177, 182
<code>\AtBeginShipoutFirst</code> 7, 445, 487	<code>\box_set_eq_drop:NN</code> 93
<code>\AtBeginShipoutInit</code> 7, 484	<code>\box_set_ht:Nn</code> 218, 227, 244, 269, 280, 298, 329
<code>\AtBeginShipoutNext</code> 7, 443, 485	<code>\box_set_wd:Nn</code> 217, 243, 268, 297
<code>\AtBeginShipoutOriginalShipout</code> . 7, 498	<code>\box_use:N</code> . 125, 223, 248, 276, 301, 331
<code>\AtBeginShipoutUpperLeft</code> 6, 490	<code>\box_wd:N</code> 193, 294, 302
<code>\AtBeginShipoutUpperLeftForeground</code> 6, 490	
<code>\AtEndDvi</code> 4, 7, 452, 457	
<code>\AtNextShipout</code> 7	
B	C
<code>\baselineskip</code> 220, 271	<code>\clearpage</code> 21
<code>\begin</code> 383	cs commands:
<code>\bfseries</code> 384	<code>\cs_gset:Npn</code> 171
bool commands:	<code>\cs_gset_eq:NN</code> 52,
<code>\bool_gset_false:N</code> 15, 81, 90	150, 164, 165, 170, 179, 183, 319, 376
<code>\bool_gset_true:N</code> 10, 121, 342	<code>\cs_gset_protected:Npx</code> 20
<code>\bool_if:NTF</code> 21, 88, 363	<code>\cs_if_exist_use:NTF</code> 311, 312, 316, 317
	<code>\cs_new:Npn</code> 54, 59, 77, 140, 145, 161,
	176, 181, 187, 190, 204, 255, 308,
	321, 335, 338, 348, 381, 500, 501, 502

\cs_new_eq:NN	239, 291, 327
.. 7, 151, 345, 347, 400, 403, 404, 499	
\cs_new_protected:Npn	249, 293
..... 23, 8, 13, 18, 341, 462	
\cs_set_eq:NN	178
..... 24, 44, 83, 95, 124, 131, 406, 408, 410, 412, 414	
\cs_set_protected:Npn	235, 237, 287, 289
\csname	401
..... 424	
D	
\DebugShipoutsOff	6, 403, 435
\DebugShipoutsOn	6, 403, 434
\DeclareRobustCommand	437
\def	396, 485, 486, 487
dim commands:	
\dim_new:N	197, 198, 199, 200
\dim_set:Nn	191, 192, 193, 194
\dim_use:N	500, 501, 502
\c_max_dim	211, 237, 262, 289
\c_zero_dim	217, 218, 219, 225, 243, 244, 245, 268, 269, 270, 297, 298, 299, 327, 329, 330
\DiscardShipoutBox	2–4, 7, 82, 400, 433, 489
E	
\end	385
\endcsname	422, 424
\enddocument	21, 22, 350
\EndIncludeInRelease	418, 455, 472, 476
\everyjob	29, 30
\EveryShipout	7
exp commands:	
\exp_args:Nx	29
\exp_not:N	31, 95, 124
\exp_not:n	30
\expandafter	423
\ExplSyntaxOff	416, 463, 503
\ExplSyntaxOn	5, 461, 498
F	
\fi	362, 399, 425
G	
\gdef	361
\global	438
group commands:	
\group_begin:	92
\group_end:	94
H	
\hbadness	236, 238, 288, 290
\hbox	1, 3, 6
hbox commands:	
\hbox:n	371
\hbox_set:Nn	168, 215, 241, 266, 295
I	
\ifcsname	422
\ifnum	5, 398
\ignorespaces	328
\IncludeInRelease	3, 419, 459, 473
int commands:	
\int_compare:nNnTF	357
..... 55, 111, 141, 351, 357	
\int_eval:n	353
\int_gincr:N	87, 102
\int_new:N	344, 346
\int_use:N	5, 104, 116, 361
\int_value:w	48, 136
\c_max_int	212, 238, 263, 290
\c_zero_int	91
iow commands:	
\iow_now:Nn	360
K	
\kern	17, 225, 275, 277, 294, 302, 323, 325
L	
\LaTeX	386, 392
\let	24, 158, 159, 160, 423, 427, 428, 429, 430, 431, 433, 434, 435, 442, 443, 445, 447, 448, 449, 452, 475, 483, 484, 489, 490, 492, 494, 496
\lineskip	221, 272
\lineskiplimit	222, 273
lua commands:	
\lua_now:n	31
\luadef	42
M	
\maxdimen	23, 349, 351, 398
\MessageBreak	99, 173, 466, 467, 468, 469
N	
\newluafunction	28
\nofiles	22
\null	374
\number	349

P	
\PackageWarning	465
\par	390
\pdfhorigin	312
\pdfvariable	311, 316
\pdfvorigin	317
pre commands:	
pre_shipout_filter	5
\PreviousTotalPages	5, 23, 396
prg commands:	
\prg_do_nothing:	164, 165, 170, 179, 183, 319
\protect ..	11, 13, 14, 83, 95, 124, 131, 151
\protected	42, 485, 486, 487
\ProvidesPackage	480
\put	2, 6, 8, 20
R	
\RawShipout	1–4, 7, 9–12, 150, 427
\ReadonlyShipoutCounter	5, 7, 27, 344, 429
\relax	24, 209, 210, 235, 236, 260, 261, 287, 288, 376
\RequirePackage	6
\Roman	5
S	
scan commands:	
\scan_stop:	44, 323, 325, 326
\setbox	438
\shipout	1–4, 7, 9, 11, 13, 14, 24, 27, 4, 52, 420, 423
shipout commands:	
\l_shipout_box	2, 10, 12, 13, 15, 17, 23, 35, 37, 50, 61, 125, 148, 177, 182, 205, 206, 213, 224, 227, 228, 232, 239, 249, 257, 264, 274, 280, 281, 284, 291, 293, 294, 300, 302
\l_shipout_box_dp_dim	2, 192, 195, 197, 228, 281, 501
\l_shipout_box_ht_dim	2, 191, 195, 197, 227, 247, 280, 500
\l_shipout_box_ht_plus_dp_dim	2, 194, 197, 213, 264, 275, 277
\l_shipout_box_wd_dim	2, 193, 197, 239, 291, 502
\shipout_debug_off:	6, 7, 404
\shipout_debug_on:	6, 7, 403
\shipout_discard:	4, 341, 400
\g_shipout_readonly_int	5, 11, 102, 104, 111, 116, 344, 353, 357, 361
\g_shipout_totalpage_int	5
\g_shipout_totalpages_int	5, 11, 87, 346
shipout internal commands:	
__shipout_add_background_box:n	178, 204, 336, 409
__shipout_add_background_-picture:n	69, 335, 413
__shipout_add_firstpage_-material:Nn	171, 187, 402, 407
__shipout_add_firstpage_-specials: ..	12, 14, 15, 110, 164, 176
__shipout_add_foreground_box:n	117, 255, 339, 411
__shipout_add_foreground_-picture:n	64, 338, 415
__shipout_debug:n ..	8, 7, 103, 115, 147
\g__shipout_debug_bool ..	6, 10, 15, 21
__shipout_debug_gset:	7
\g__shipout_discard_bool	81, 88, 90, 201, 342
__shipout_drop_firstpage_-specials: ..	14, 15, 126, 165, 176
__shipout_excuse_extra_page:	373, 381
__shipout_execute:	10, 46, 52
__shipout_execute_cont:	57, 59
__shipout_execute_main_cont:Nnn	10, 13, 60, 77, 146
__shipout_execute_nohooks_cont:	143, 145
__shipout_execute_raw: ..	13, 134, 150
__shipout_execute_test_level:	49, 54
__shipout_execute_test_level_-raw:	134
__shipout_finalize_box:	26, 123
\l__shipout_firstpage_box	15, 168, 178, 185
__shipout_get_box_size:N	16, 85, 107, 190, 205
\l__shipout_group_level_t1	47, 53, 56, 135, 142
\c__shipout_horigin_t1	308, 323
__shipout_init_page_origins:	308, 322
\g__shipout_lastpage_handled_-bool	121, 186, 363
__shipout_picture_overlay:n	321, 336, 339
\l__shipout_raw_box	12, 25, 138, 146, 148, 177, 182
__shipout_run_firstpage_hook:	12, 14, 15, 108, 161
\l__shipout_saved_badness_t1	202, 208, 216, 229, 234, 242, 251, 259, 267, 279, 286, 296, 304

_shipout_saved_protect:	83, 131, 151	\@latex@info@no@line	89
\I_shipout_tmp_box	202, 215, 217, 218, 219, 223, 241, 243, 244, 245, 248, 266, 268, 269, 270, 276, 295, 297, 298, 299, 301, 327, 329, 330, 331	\@latex@warning	172
\c_shipout_vorigin_tl	308, 325	\@latex@warning@no@line	79, 98
shipout/after	2, 152	\@undefined	427,
shipout/background	2, 152	428, 429, 430, 431, 433, 434, 435, 442, 443, 445, 447, 448, 449, 452, 475	
shipout/before	2, 152	\c@totalpages	346, 430
shipout/firstpage	2, 152	\declare@file@substitution	506
shipout/foreground	2, 152	\disable@package@load	464
shipout/lastpage	2, 152	\g@addto@macro	350, 356, 397
\ShipoutBox	1–3, 7, 15, 23, 428, 483	\if@filesw	359
\ShipoutBoxDepth	448, 500	\reenable@package@load	25, 453
\ShipoutBoxHeight	27, 447, 500	\set@typeset@protect	84, 127
\ShipoutBoxWidth	449, 500	\undeclare@...	25
skip commands:		tex commands:	
\skip_zero:N	220, 221, 222, 271, 272, 273	\tex_afterassignment:D	49, 137
\space	105	\tex_aftergroup:D	10, 57, 143
\special	3, 12, 14, 15, 27	\tex_currentgrouplevel:D	
\string	173, 361	48, 56, 136, 142	
sys commands:		\tex_deadcycles:D	91
\sys_if_engine_luatex:TF	26	\tex_setbox:D	50, 138
T		\tex_shipout:D	125, 369, 499
T _E X and L ^A T _E X 2 _ε commands:		\tex_vss:D	332
\@abspage@last	21, 23, 105, 111, 349, 351, 353, 361, 398, 399	\textheight	369
\@auxout	360	\the	34, 35, 37, 42, 209, 210, 235, 236, 260, 261, 287, 288
\@begindvi	8	\thepage	21
\@begindvibox	3, 438, 439	\thetotalpages	5, 21, 348, 431
\@cclv	7	tl commands:	
\@empty	158, 159, 160, 484	\tl_const:Nn	309, 314
\@expl@@@shipout@add@background@box@on	406, 491	\tl_if_empty_p:N	68, 114, 367
\@expl@@@shipout@add@background@picture@on	406, 495	\tl_new:N	53, 203
\@expl@@@shipout@add@firstpage@material@Nn	406, 488	\tl_set:Nn	47, 135, 208, 234, 259, 286
\@expl@@@shipout@add@foreground@box@on	406, 493	totalpages	5
\@expl@@@shipout@add@foreground@picture@on	406, 497	\typeset	4, 104, 115, 147
\@extra@page@added	376	U	
\@kernel@after@enddocument	350	\unitlength	2, 3, 19, 326
\@kernel@after@enddocument@afterlastpage	356	\unvbox	439
\@kernel@after@shipout@background	10, 72, 158	use commands:	
\@kernel@after@shipout@lastpage	22, 114, 119, 158, 367, 372	\use_none:n	7
\@kernel@before@begindocument	396	\UseHook	118, 168, 371
\@kernel@before@shipout@background	10, 68, 70, 158	\usepackage	6
V		vbox commands:	
		\vbadness	17, 210, 212, 261, 263
		\vbox	1, 16, 369, 439
		\vbox_set_to_ht:Nnn	213, 264
		\vbox_to_zero:n	324
		\vbox_unpack:N	224, 274
		\vfil	382, 394
		\vfuzz	17, 209, 211, 260, 262

W **X**
\write 3, 13 \xdef 349, 353, 399