

Loading multiple data models with biblatex

Maïeul Rouquette Version 1.0.1
maieul <at> maieul <dot> net 26/04/2015

Contents

1 Introduction	1	4 Credits	2
2 Use	1	5 Change history	2
3 For developers	2		

1 Introduction

Datamodel in biblatex are conceived to be distributed as a part of citations and bibliographic styles¹. However, sometime, the modification in datamodel is too tiny to need a new style, and can be easily integrated to standard biblatex styles. That is the case in the two projects *biblatex-realauthor* and *biblatex-manuscripts-philology*. Because of biblatex conception of datamodel distribution, it's not possible to load both datamodels of *biblatex-realauthor* and *biblatex-manuscripts-philology*.

This package *biblatex-multiple-dm* allows to load multiple datamodel without creating a full biblatex style.

2 Use

The package must be loaded before the biblatex package. It's loaded with two options:

tools which is a comma separated list of the datamodels to be loaded.

bibstyle which is the main bibstyle to be loaded.

For example:

```
\usepackage[tools={realauthor,manuscripts},bibstyle=verbose]{biblatex-multiple-dm}
```

After that, the biblatex package must be loaded with the bibstyle option equal to `multiple-dm`:

```
\usepackage[bibstyle=multiple-dm,citestyle=verbose-trad2]{biblatex}
```

¹See: <https://github.com/plk/biblatex/issues/220#issuecomment-37761639>.

3 For developers

If one developer wants to allow his/her “bibliography style” be compatible with `biblatex-multiple-dm`, he/she has just to try the existing of `\biblatexmultiple@bibstyle` macro when loading primary bibstyle:

```
\ifdef{\biblatexmultiple@bibstyle}
  {\RequireBibliographyStyle{\biblatexmultiple@bibstyle}}
  {\RequireBibliographyStyle{verbose}}
```

4 Credits

This package was created for Maïeul Rouquette’s phd dissertation² in 2014. It is licensed on the *TeX Project Public License*³. It’s freely inspired by a code of Oleg Domanov⁴.

All issues can be submitted, in French or English, in the GitHub issues page⁵.

5 Change history

1.0.1 2014-06-25

Show the correct file version with `\ProvidesFile`.

1.0.0 2014-06-25

First public release.

²<http://apocryphes.hypotheses.org>.

³<http://latex-project.org/lppl/lppl-1-3c.html>.

⁴<http://tex.stackexchange.com/a/154568/7712>.

⁵<https://github.com/maieul/biblatex-multiple-dm/issues>.